



Z-OX

Solvent Based Concrete Seal

This modern advancement in floor care technology provides a durable, semi-permanent concrete finish. The outstanding leveling characteristics enable application using a single-pass applicator. Conseal WB Concrete Seal produces a uniform film for the ultimate in beauty and performance.

■ PHYSICAL PROPERTIES

APPEARANCE: White Emulsion
SPECIFIC GRAVITY: 1.023
ODOR: Acrylic
pH (Conc.): 7 to 9
FLASH POINT: N/A (WATER-BASED LIQUID)

■ PACKAGING

Z-OX is available in 4x1 gallon cases, 5 gallon pails and 55 gallon drums.

■ ADDITIONAL INFORMATION

If you need additional information, please contact our corporate office at 816-471-3602. For a Material Safety Data Sheet go to www.chemicaluniverse.com.

■ DIRECTIONS

Recoating previously finished floors: Clean floors by damp mopping or wet scrubbing and allow to dry. To abrade the floor use a stiff bristle brush with a scrubber or buffer to remove soils, contamination and black marks. If using a rotary floor machine overlapping 1 to 2". Tack or rinse the floor with clear water to remove dust residues. Apply finish with applicator or roller. In using a single pass applicator, give special attention to moving at a slow walk and run 1" to 2" puddle in front of the applicator head, overlapping each pass approximately 5" angling the applicator head to allow excess finish to tail off the side toward the unfinished floor where the excess can be further leveled on the next pass.

■ SAFE STORAGE & HANDLING

Combustible liquid irritant. Contains petroleum hydrocarbons. Harmful or fatal if swallowed. Keep away from heat and open flame. Close container after each use. Use with adequate ventilation. Avoid prolonged breathing of vapor. Avoid prolonged or repeated contact with skin.