



FLOAT SOLV

Lift Station Degreaser

Float Solv is a unique blend of naturally occurring soy and citrus solvents specifically designed for the maintenance of lift stations and grease traps. The properties of this chemical allow it to float and suspend on "top" of the water. As the control valves and floats inside a lift station raise and lower the level of sewage, Float Solv stays on top cleaning and degreasing the side walls and controls of the lift station.

Float Solv is harmless to all rotors, seals, "O" rings and control valves, attacking only the undesirable grease and sludge that accumulates in these areas. It may be necessary to clean and degrease the area before applying Float Solv as a maintainer. Consult with your representative for proper application and dosage. Cleans and Degreases walls and mechanisms automatically. Use on sides of tanks, in sewer lines, ect. Easy to use - just pour in. Will not freeze.

■ PHYSICAL PROPERTIES

APPEARANCE: Clear Liquid
SPECIFIC GRAVITY: 0.807
ODOR: Kerosene
pH (Conc.): 5 to 7
FLASH POINT: 35° F

■ PACKAGING

Float Solv is available in 5 gallon pails and 55 gallon drums.

■ ADDITIONAL INFORMATION

If you need additional information, please contact our corporate office at 816-471-3602. For a Material Safety Data Sheet go to www.chemicaluniverse.com.

■ DIRECTIONS

DIRECTIONS FOR USE:

FOR GREASE TRAPS: To keep clean, fresh smelling and free flowing, add enough product to maintain a 1 to 3 inch layer above the water level. (Two quarts will cover 60 square inches at a depth of 2 inches.) If trap is heavily loaded with grease, it must be cleaned out manually before adding this product.

FOR SEWAGE PLANTS: Add to lift station. Depending on quantity of accumulated scum, grease and oils; Pour in enough product to maintain a blanket layer of 1 to 3 inches. It takes approximately one gallon of product per square foot.

■ SAFE STORAGE & HANDLING

Caution: This product is intended for Industrial and Institutional use. Although this is a mild cleaning agent, It can cause irritation to eyes and skin. Avoid contact by wearing protective devices such as safety glasses and rubber gloves. If contact to eyes or skin, flush with water for 10-15 minutes. If irritation persists, seek medical attention. Always read the Material Safety Data Sheet for additional precautions before using this product.

WARNING: COMBUSTIBLE: DO NOT USE NEAR AN OPEN FLAME. HARMFUL IF SWALLOWED.