



GREASE BAN

Organic Solvent Degreaser

Grease Ban is a degreaser for use in sewage treatment plants and waste water systems. This product is an easy to use liquid formulated to eliminate troubles caused by fats, grease and scum.

■ PHYSICAL PROPERTIES

APPEARANCE: Clear Liquid
SPECIFIC GRAVITY: 1.057
ODOR: Characteristic
pH (Conc.): N/A (Solvent-Based)
FLASH POINT: 186° F

■ PACKAGING

Grease Ban is available in 5 gallon pails and 55 gallon drums.

■ ADDITIONAL INFORMATION

If you need additional information, please contact our corporate office at 816-471-3602. For a Material Safety Data Sheet go to www.chemicaluniverse.com.

■ DIRECTIONS

Add Grease Ban directly to any stage of treatment. Amount required will depend on task to be accomplished.
DIGESTERS: Add directly to digesters before recirculating to dissolve scum blanket.
TRICKLING FILTER: Drip into dosing tank ahead of trickling filters to remove grease and scum from filter media or stones. Will not interfere with algae growth, eliminates puddling of the bed. Will not harm larvae.
FLOATING DIGESTER COVERS: Spray GREASE BAN around edge of cover and wash down with water to release stuck floating digester cover.
WET WELLS of PUMPING (LIFT) STATIONS, PIPELINES from CLARIFIER to DIGESTER, FORCE MAINS: Add GREASE BAN to sewage to prevent scum and grease build-up which causes line stoppages.

■ SAFE STORAGE & HANDLING

WARNING: COMBUSTIBLE: DO NOT USE NEAR AN OPEN FLAME. HARMFUL IF SWALLOWED.
This product is intended for Industrial and institutional use. It can cause irritation and/or damage to eyes and skin. Avoid contact by wearing protective devices such as safety glasses and rubber gloves. If contact to eyes or skin, flush with water for 10-15 minutes. If irritation persists, seek medical attention. Always read the Material Safety Data Sheet for additional precautions before using this product.