

LAMINATE SEALER

The Floor Sealer

Laminate Sealer is designed to be used as a base coat which will fill-in tile imperfections and insure the bonding process of re-coating tile floors. Laminate is a blend of acrylic polymers and leveling agents. It is formulated to provide a more secure bond to tile and increase floor finish coverage rate.

■ PHYSICAL PROPERTIES

APPEARANCE: White Emulsion

SPECIFIC GRAVITY: 1.023

ODOR: Sweet Acrylic

pH (Conc.): 7 to 9

FLASH POINT: N/A (WATER-BASED LIQUID)

■ PACKAGING

Laminate Sealer is available in a 4X1 gallon case, 5 gallon pail, and 55 gallon drum.

■ ADDITIONAL INFORMATION

If you need additional information, please contact our corporate office at 816-471-3602. For a Material Safety Data Sheet go to www.chemicaluniverse.com.

■ DIRECTIONS

1. Thoroughly clean the floor and remove all old wax or finish using a solution of a concentrated wax and finish stripper. Pay particular attention to corners and baseboards to ensure that all old coatings have been removed.
2. Scrub rinse well with clear water; pick up with a wet vac or mop and allow to dry.
3. Apply the Laminate sealer using a rayon mop or gravity fed applicator.
4. If floor has a uniform luster, sufficient sealer has been applied. If not, a second coat should be applied in the same manner. Be sure the previous coat is "tack free" before applying floor finish.
5. Apply 3 to 5 coats of floor finish.

COVERAGE: 800 sq. ft. per gallon

■ SAFE STORAGE & HANDLING

Caution: This product is intended for Industrial and Institutional use. Although this is a mild cleaning agent, It can cause irritation to eyes and skin. Avoid contact by wearing protective devises such as safety glasses and rubber gloves. If contact to eyes or skin, flush with water for 10-15 minutes. If irritation persists, seek medical attention. Always read the Material Safety Data Sheet for additional precautions before using this product.