



ULTRA STRIP

Extra Active Stripper

Ultra Strip is a special blend of water-soluble solvents and surfactants designed to emulsify multiple coats of floor finish. Ultra Strip is effective at removing as many as 10 coats of floor finish. It should be used on vinyl composition tile and other floors that will not be harmed by water-based solvents

■ PHYSICAL PROPERTIES

APPEARANCE: Clear Liquid
SPECIFIC GRAVITY: 1.023
ODOR: Butyl
pH (Conc.): 10 to 12
FLASH POINT: N/A (WATER-BASED LIQUID)

■ PACKAGING

Ultra Strip is available in a 4X1 gallon case, 5 gallon pail, and 55 gallon drum.

■ ADDITIONAL INFORMATION

If you need additional information, please contact our corporate office at 816-471-3602. For a Material Safety Data Sheet go to www.chemicaluniverse.com.

■ DIRECTIONS

1. To achieve best performance, experiment in small test area with various dilutions before applying generally.
2. Dilute before using. Do not use on painted surfaces or wooden floors. Use cautiously for stripping linoleum, rubber or asphalt tile as stripper may cause bleaching, softening or bleeding.
3. Rinse immediately with water and pick up. Wipe up any spills or splashes from baseboards or painted surfaces immediately.

For Use:

1. For normal problem floors, dilute 1 part stripper to 4 parts warm water. Apply to small inconspicuous test area before doing entire floor. Dilution ratios ranging from 1:4 to 1:10 may be necessary depending on the number of coats of old finish.
2. Using determined dilution ratio, apply to small area of flooring (approx. 50-100 sq. ft.) Permit solution to remain on floor approximately 5 minutes before scrubbing. Do not allow solution to dry on floor.
3. Scrub thoroughly with machine and stripping pad. Pick up solution immediately with wet-dry vac or mop.
4. Rinse well with clear water.
5. Do not apply sealer or finish until floor is thoroughly dry.

Automatic Scrubbers

Use the double pass method for best results. Apply stripping solution, normally 1 part stripper to 10 parts water. (Test in small area prior to stripping floor). Then strip with machine.

■ SAFE STORAGE & HANDLING

Warning: This product is intended for Industrial and Institutional use. It can cause irritation and/or damage to eyes and skin. Avoid contact by wearing protective devices such as safety glasses and rubber gloves. If contact to eyes or skin, flush with water for 10-15 minutes. If irritation persists, seek medical attention. Always read the Material Safety Data Sheet for additional precautions before using this product.