



# WOOD SEAL WB

## Water Based Wood Finish

Wood Seal WB is a cross-linked, water-based coating, based on the latest polymer technology. It is non yellowing, has low odor, is non flammable and meets current V.O.C. regs. Wood Seal WB can be applied over existing solvent based finishes.

### ■ PHYSICAL PROPERTIES

APPEARANCE: Milky White Liquid  
 SPECIFIC GRAVITY: 1.012  
 ODOR: Characteristic  
 pH (Conc.): 6 to 8  
 FLASH POINT: N/A (WATER-BASED LIQUID)  
 Solid %: 25

### ■ PACKAGING

Wood Seal WB is available in 4x1 gallon cases, 5 gallon pails and 55 gallon drums.

### ■ ADDITIONAL INFORMATION

If you need additional information, please contact our corporate office at 816-471-3602. For a Material Safety Data Sheet go to [www.chemicaluniverse.com](http://www.chemicaluniverse.com).

### ■ DIRECTIONS

1. Do not apply when temperature is over 90deg.or when humidity is over 80%.
2. Before applying Wood Seal WB, close all doors and windows and shut down air-moving systems.
3. Do not apply more than two coats in one day.
4. Apply Wood Seal WB using a weighted application bar, lambswool applicator or mechanical applicator. Apply with the grain of the wood. Allow to dry until no tackiness is present before applying additional coats. If more than 24 hours has expired, a light screening process will need to be performed if additional coats are desired. Two coats of Wood Seal WB will give you a high level performance when applied over an existing solvent-based finish.
5. After the last coat has been applied, allow to dry overnight with some ventilation before light foot traffic and 48 hours before heavy foot traffic.

#### Maintenance:

- 1.Dust mop at least daily, with a mop treated with a water-based dust mop treatment. Be sure to treat the mop at least 24 hrs. before using it.
- 2.Damp mop at least weekly with Neutral Cleaner.
3. To restore glow use Sure Step Red Restorer according to label instructions and burnish with a high speed buffer.

### ■ SAFE STORAGE & HANDLING

Caution: This product is intended for Industrial and Institutional use. Although this is a mild cleaning agent, It can cause irritation to eyes and skin. Avoid contact by wearing protective devises such as safety glasses and rubber gloves. If contact to eyes or skin, flush with water for 10-15 minutes. If irritation persists, seek medical attention. Always read the Material Safety Data Sheet for additional precautions before using this product.