



PHYSICAL PROPERTIES

Appearance: Clear Liquid

Specific Gravity: 1.02

Odor: Butyl

Ph (Conc.): 13-13.5

Flash Point: >212°F (100°C)

PACKAGING

4X1 gal, 5 gal, 55 gal

F-900

HEAVY DUTY ALKALINE CLEANER

ABOUT THIS PRODUCT

F-900 is a high foaming cleaner recommended for foam cleaning walls, ceilings, floors and stainless steel equipment. This product is effective at removing carbon based soils. It is a high foaming formula designed to cling to vertical surfaces for removal of baked-on soils. F-900 is effective in bakeries, snack food plants, oil processors, supermarkets and meat, seafood, vegetable, poultry and other food processors.

- High Foaming For Enhanced Attack On Complex Food Soils
- Specially Formulated To Dissolve Fats, Oils And Grease
- Deodorizes As It Cleans
- For Use On Walls, Floors And Stainless Steel Equipment

DIRECTIONS

Dilute this product at a rate of 1:10 to 1:30 with water and apply through foam generating equipment. Let foam solution dwell 5-15 minutes, agitate if needed and follow with a potable water rinse. A potable water rinse is required for all food contact surfaces. Not for use on aluminum, galvanized steel or other soft metals.

PRECAUTIONARY STATEMENTS

Prevention: Wear eye protection/face protection. Wash hands and exposed skin thoroughly after handling. Wear protective gloves. **Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor/ medical professional. IF ON SKIN: Wash with plenty of water for at least 15 minutes. Specific treatment (see section 4 on the Safety Data Sheet). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.



SCAN FOR SDS