



PHYSICAL PROPERTIES

Appearance: Clear Liquid

Specific Gravity: 1.02

Odor: Butyl

Ph (Conc.): 13-13.5

Flash Point: >212°F (100°C)

PACKAGING

4X1 gal, 5 gal, 55 gal

F-902

FOAMING ALKALINE CLEANER

ABOUT THIS PRODUCT

For use in removing heavy accumulations of grease, carbonized soils, and oils from smokehouse and food plant surfaces. May be used in foamers, steam cleaners, or pressure washers. Completely free-rinsing. Effective in hard or soft water. Essentially odorless in use. No additional foam booster is required.

DIRECTIONS

FOR FOAM CLEANING: Mix 2 to 5 ounces per gallon of hot water. Apply as a foam to all surfaces. Allow contact time of 5 to 10 minutes and scrub thoroughly with brush. Do not allow solution to dry. Rinse all surfaces thoroughly.

FOR MEDIUM-DUTY STEAM CLEANING: Dilute 2 to 6 ounces per gallon of water and apply with a steam cleaner. Rinse thoroughly with water.

FOR HIGH PRESSURE WASHING: Dilute 2 to 4 ounces per gallon of water and apply with pressure sprayer. Rinse surfaces thoroughly with water.

NOTE: For use on ferrous metals only. DO NOT use on galvanized metals, aluminum, or other alkali sensitive surfaces as damage may occur. Avoid contact with painted surfaces.

PRECAUTIONARY STATEMENTS

Prevention: Wear eye protection/face protection. Wash hands and exposed skin thoroughly after handling. Wear protective gloves. **Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor/ medical professional. IF ON SKIN: Wash with plenty of water for at least 15 minutes. Specific treatment (see section 4 on the Safety Data Sheet). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.



SCAN FOR SDS