



PHYSICAL PROPERTIES

Appearance: Light Amber Liquid

Specific Gravity: 0.9

Odor: Butyl

Ph (Conc.): N/A

Flash Point: 150°F (66°C) estimated.

PACKAGING

12X32 oz, 4X1 gal,
5 gal, 55 gal

Premium Mastic Remover

H.D. MASTIC REMOVER & DEGREASER

ABOUT THIS PRODUCT

Premium Mastic Remover is a unique blend of natural-based solvents and cleaning agents specifically designed for the removal of glue, mastics, asphalt, tar and grease. It can also be used in the maintenance of lift stations and grease traps.

Cleans and degreases all surfaces and tools after application. Easy to use-just pour in. Will not freeze.

Use In: Mastic And Adhesive Remover, Asphalt Applications, Lift Stations, Waste Treatment Plants

DIRECTIONS

For Mastic Removal: Liberally apply to the floor surface. Let product sit until the adhesive or mastic is liquified. Remove by scraping solution to a central point and adding clay-based oil dry to absorb the solution.

PRECAUTIONARY STATEMENTS

Prevention: Keep away from flames and hot surfaces. No smoking. Wear protective gloves/eye protection/face protection. Wash hands and exposed skin thoroughly after handling. **Response:** In case of fire: Use water fog, foam or carbon dioxide (CO₂) to extinguish. Call a POISON CENTER/doctor/medical professional if you feel unwell. **IF ON SKIN:** Wash with plenty soap and water. Specific treatment: See section 4 on the Safety Data Sheet. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. **IF SWALLOWED:** Immediately call a POISON CENTER/doctor/medical professional. Do NOT induce vomiting. **Storage:** Store in a well-ventilated place. Keep cool. Store locked up. **Disposal:** Dispose of contents/container in accordance with local/regional/ national/ international regulations.

