



7

FLOOR FINISH RESTORER



PHYSICAL PROPERTIES

Appearance: Red Liquid
Specific Gravity: 1.0
Odor: Characteristic
Ph (Conc.): 8-9
Flash Point: >212°F (100°C)

PACKAGING

4X64 oz

[VIEW DEMO VIDEO](#)

ABOUT THIS PRODUCT

LockNLoad Jr. #7 Floor Finish Restorer should be used as a regular part of propane and other high speed floor maintenance programs to greatly reduce labor and provide outstanding results.

Mop and Burnish Method: Damp mop floor with solution, evenly applying a thin coat. Let floor dry thoroughly, burnish floor with a high speed floor machine and the proper burnish pad.

Automatic Scrubber Method: Scrub the floor, picking up solution and use a detail mop as necessary. Let the floor dry thoroughly and burnish with a propane or other high speed floor equipment.

DIRECTIONS

To dispense the product, attach the LockNLoad Jr. dilution unit or adapter cap onto the Green insert in the opening of the bottle. The dispensing system is factory set to properly dilute the concentrate with water. For a water driven system, connect the system to a water line to dilute the product.

LockNLoad Jr. products are designed to be used with a dilution system. Using the dispensing system will ensure that the concentrate is diluted correctly. The green insert in the opening of the container should never be removed. If the green insert has been removed, the contents of the container and the container should be properly disposed of.

PRECAUTIONARY STATEMENTS

Prevention: Wash hands and exposed skin thoroughly after handling. Wear eye protection/face protection. **Response:** If skin irritation occurs: Get medical advice/ attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. If eye irritation persists: Get medical advice/ attention.

